



The Alerton® VisualLogic® VLC-853-E is a versatile, BACnet-compliant, fully programmable field controller designed for central plant systems, air handling units, clean rooms, fume hoods, large terminal units, and similar control and process equipment. As a native BACnet controller, it integrates seamlessly with your BACnet system, communicating at up to 115 Kbps on a BACnet MS/TP LAN.

The VLC-853-E supports the Alerton Microtouch™, as well as the BACtalk® Microset, Microset II, and Microset 4 intelligent wall sensors, which offer convenient data display, setpoint adjustment, and technician access to equipment setup parameters.

All VLC-853-E control logic is programmed using Alerton's easy-to-learn graphical programming language, VisualLogic™. Programming and setup data are stored in non-volatile flash memory, ensuring stable and reliable operation.

High-resolution 16-bit universal inputs are auto-selectable for thermistor, dry contact, pulse, 0-5 V, 0-10 V, or 4-20 mA.

High-resolution 16-bit analog outputs are auto-selectable for 0-10 V or 0-20 mA.

## VISUALLOGIC® UNITARY FIELD CONTROLLER

### FEATURES AND HIGHLIGHTS

- Fully BACnet-compliant on MS/TP LAN at up to 115.2 Kbps.
- Programmable control logic can be field-modified.
- Downloadable operating code to allow for future software improvements.
- 32-bit processor architecture with all program data backed up in nonvolatile flash memory.
- High-speed processing of DDC program, with an internal logical loop time of 100 msec.
- Backwards compatible with older VLC-853 and VLC-853C3 models.

### APPLICATIONS

Recommended for central plant systems, air handling units, large terminal units, and similar control and process equipment.



### VLC-853-E

UI	HBO	GBO	RO	AO	AF	F
UNIVERSAL INPUTS	HOT SWITCHED TRIAC BINARY OUTPUTS	GROUND SWITCHED BINARY OUTPUTS	RELAY OUTPUT	ANALOG OUTPUTS	AIR-FLOW SENSOR	FILTER

**TECHNICAL DATA**

**POWER** – 24 VAC @ 50-60 Hz. 15 VA minimum (maximum 97 VA with loads). Half-wave rectified.

**INPUTS** – 16-bit universal inputs accept 3k (Ibex) or 10k thermistor (type II), dry contact, 0-20 mA, 0-10 V, 0-5V, or dry-contact pulse. External 250-ohm resistor required for 0-20 mA inputs. Pulse input maximum frequency of 100 Hz. Pulse input minimum duty cycle 5mS ON / 5mS OFF (pulse input not supported on IN-0).

**POWER OUTPUT FOR EXTERNAL SENSORS** – 20 VDC  $\pm 10\%$  @100 mA maximum

**BINARY OUTPUTS** – Triacs rated 24 VAC @ 50/60 Hz, 500 mA continuous and 800 mA (AC rms) for 60 milliseconds.

**ANALOG OUTPUTS** – 16-bit universal analog outputs support Voltage Mode: 0-10 VDC @ 10 mA maximum (1k ohm minimum); Current Mode: 4-20 mA @ 550 ohms Maximum.

**MICROSET** – Supports BACtalk® Microset, Microset II, or Microset 4 on input 0 (IN-0).

**INPUT/OUTPUT TERMINATIONS** – Removable header-type screw terminals accept 14-24 AWG wire.

**MAX DIMENSIONS** – 4.9" (125mm) H x 5.4" (137mm) W x 1.4" (36mm) D

**MOUNTING** – Screw mounting

**ENVIRONMENTAL** – 0 to 158°F (-17 to 70°C) / 5 to 95%RH, non-condensing

**COMMUNICATIONS** – EIA-485 (RS-485) over twisted shielded-pair (TSP); auto-baud switching (9.6kbps, 19.2kbps, 38.4kbps, 76.8kbps, or 115.2kbps); communication status LED.

**PROTOCOLS** – BACnet MS/TP (master)

**PROGRAMMING** – Supports Alerton's BD4 DDC file format using Alerton's VisualLogic® toolset.

**MICROPROCESSOR** – 32-bit ARM Cortex-M4F, 80 MHz

**MEMORY** – 512 MB non-volatile flash.

**SECURITY** – Integrated secure boot prevents loading of tampered firmware.

**ORDERING INFORMATION****ITEM NUMBER**

VLC-853-E ALERTON VISUALLOGIC  
CONTROLLER BACNET

**CERTIFICATION AND CONFORMANCE**

**BACNET CONFORMANCE** – An application specific controller (ASC) level device; tested and approved by BTL. See Protocol Implementation Conformance Statement (PICS).

**UL** – Listed Underwriters Laboratory for Open Energy Management Equipment (PAZX) under the UL Standard for Safety 916; listing includes both U.S. and Canadian certification.

**EMC** – EMC Directive 89/336/EEC (European CE Mark).

**FCC** – This device complies with part 15 of the FCC Rules. Operation is subject to the following two conditions: (1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.



16201 25th Avenue W, Lynnwood, WA 98087  
Telephone: (425) 921-4900 / Fax: (425) 921-4872  
alerton.com / sales@alerton.com